SUNPARADISE®

ORDER FORM

WINDOWS, FIXED GLAZING **SUPERTHERM 80**

Customer

Reference

Delivery WK No. [min 4 weeks]

E-Mail:

Place/Date

Number of enclosures (Plan/Sketch):

Signature

Glazing viewed from inside

☐ Fixed glazing

○ Bottom hung window

○ Left side hung window

○ Double-wing window

First-opening: ○ Left ○ Right

○ Right side hung window

○ Double-wing window with tilt and turn casement Left

○ Left sinde tilt and turn window

○ Double-wing window with tilt and turn casement Right

○ Right side tilt and turn window

☐ with frame latch

Plan/Sketch viewed from inside

Dimensions Width(mm)

Height(mm) Transom height [top] (mm)

Skylight opener Snap latch standard

Draw-cord ○ Left ○ Right

Crank rod ○ Left ○ Right

○ 1500mm ○ 2000mm ○ other lengths(mm)

Electric motor with chain-drive ○ 24V DC ○ 230V AC

Locking bolt height ○ Centre position

○ Standard: 1100mm ○ Other:min.300(mm) from u/s floor guide

Alu-frame Inside ○ Natur. anod. ○ RAL 9010 ○ Other Colour

Outside ○ Natur. anod. ○ RAL 9010 ○ Other Colour

Glazing ○ With ○ Without ○ double glazed 24mm ○ prepared for (mm)

Ironmongery Inside ○ Black ○ White ○ Aluminium col.

Outside ○ Black ○ White ○ Aluminium col.

EPDM/TPV Inside ○ Black ○ White ○ Grey

Gaskets Outside ○ Black ○ White ○ Grey ☐ silicone-free

Compensation profile* 54mm ☐ Top ☐ Bottom ☐ Left** ☐ Right**

Remark

***Watch the height!** ****Inside view**

FORM_V_ST_80

12–2008